













- Procedia Engineering*, vol. 191, pp. 332-341, 2017.
- [4] S. Arora and B. Mishra, "Investigation of the failure mode of shale rocks in biaxial and triaxial compression tests", *International Journal of Rock Mechanics & Mining Sciences*, vol.79, pp. 109-123, 2015.
- [5] P. Liolios, and G. Exadaktylos, "Comparison of a hyperbolic failure criterion with established failure criteria for cohesive-frictional materials", *International Journal of Rock Mechanics and Mining Sciences*, vol. 63, pp. 12-26, 2013.
- [6] L.-H. Zhao, S. Zuo, L. Li, Y.-L. Lin, and Y.-B. Zhang, "System reliability analysis of plane slide crack induced using barton-bandis failure criterion", *International Journal of Rock Mechanics and Mining Sciences*, vol. 88, pp. 1-11, 2016.
- [7] L. Zubillaga, A. Turon, J. Renart, J. Costa, P. and Linde, "An experimental study on matrix crack induced delamination in composite laminates", *Composite Structures*, vol. 127, pp. 10-17, 2015.
- [8] S. Zhi, and D. Elsworth, "The role of gas desorption on gas outbursts in underground mining of coal", *Journal of Geomech. Geophys. Geo-energ. Geo-resour*, vol. 2, pp. 151-171, 2016.
- [9] Supandi, Zakaria Z., Sukiyah E. and Sudradjat A., The Correlation of Exposure Time and Claystone Properties at The Warukin Formation Indonesia, *International Journal of GEOMATE*, Vol.15, Issue 52, 2018, pp. 160-167.
- [10] Supandi, Zakaria Z., Sukiyah E. and Sudradjat A., The Influence of Kaolinite-Illite Toward Mechanical Properties of Claystone, *Open Geosciences*, Vo.11, Issue 1, 2019, pp.440-446.
- [11] Supandi, H.G. Hartono., Geomechanic Properties and Provenance Analysis of Quartz Sandstone From The Warukin Formation, *International Journal of GEOMATE*, Vol.18, Issue 66, 2020, pp. 140-149.
- [12] M.A. Ismael, H.F. Imam, and Y. El-Shayeb, "A simplified approach to directly consider intact rock anisotropy in hoek-brown failure criterion", *Journal of Rock Mechanics and Geotechnical Engineering*, vol. 6, pp. 486-492, 2014.
- [13] L. Chen, J.F. Shao, Q.Z. Zhu, and G. Duveau, "Induced anisotropic damage and plasticity initially anisotropic sedimentary rocks", *International Journal of Rock Mechanics & Mining Sciences*, vol. 51, pp. 13-23, 2012.
- [14] D. Hu, H. Zhou, F. Zhang, J. Shao, and J. Zhang, "Modeling of inherent anisotropic behavior of partially saturated clayey rocks", *Computer and Geotechnics*, vol. 48, pp. 29-40, 2013.
- [15] O. Saeidi, V. Rasouli, R.G. Vaneghi, R. Gholami, and S.R. Torabi, "A modified failure criterion for transversely isotropic rock", *Geoscience Frontiers*, vol. 5, pp. 215-225, 2013.
- [16] B. Bahrami, S. Mohsenpour, M.A. Miri, and R. Mirhaseli, "Quantitative comparison of fifteen rock failure criteria constrained by polyaxial test data", *Journal of Petroleum Sciences and Engineering*, vol. 159, pp. 564-580, 2017.
- [17] J.P. Meyer, and J.F. Labuz, "Linier failure criteria with three principal stresses", *International Journal of Rock Mechanics and Mining Sciences*, vol. 60, pp. 180-187, 2013.
- [18] C. Zhang, X. Chen, W. Fan, and J. Zhao, "A new unified failure criterion for unsaturated soils", *Environ Earth Sciences*, vol. 74, pp. 3345-3356, 2015.
- [19] R. Rahimi, and R. Nygaard, "Comparison of rock failure criteria in predicting borehole shear failure", *International Journal of Rock Mechanics and Mining Sciences*, vol. 79, pp. 29-40, 2015.
- [20] Y. Yugui, G. Feng, C. Hongmei, and H. Peng, "Energy dissipation and failure criterion of artificial frozen soil", *Journal Cold Regions Science and Technology*, vol.129, pp.137-144, 2016.
- [21] X. Ma, J.W. Rudnicki, and B.C. Haimson, "The application of matsuo-nakai-lade-duncan failure criterion to two porous sandstones", *International Journal of Rock Mechanics and Mining Sciences*, vol. 92, pp. 9-18, 2017.
- [22] W. Chen, H. Konietzky, X. Tan, and T. Fruhwirt, "Pre-failure damage analysis for brittle rock under triaxial compression", *Journal Computer and Geotechnics*, vol. 74, pp. 45-55, 2016.
- [23] D.J. Robert, "A modified mohr-coulomb model to simulate the behaviour of pipelines in unsaturated soils", *Journal Computer and Geotechnics*, vol. 91, pp. 146-160, 2017.
- [24] S.I. Woo, H. Seo, and J. Kim, "Critical-state-based mohr-coulomb plasticity model for sands", *Computers and Geotechnics*, vol.92, pp. 179-185, 2017.
- [25] Y. Tian, and Y.-P. Yao, "A simple method to describe three-dimensional anisotropic failure of soils", *Journal Computer and Geotechnics*, vol.92, pp. 210-219, 2017.
- [26] A. Zhou, S. Wu, J. Li, and D. Sheng, "Including degree of capillary saturation into constitutive modelling of unsaturated soils", *Journal Computer and Geotechnics*, vol. 95, pp. 82-98, 2018.
- [27] Y. Zhu, "A micromechanics-based damage constitutive model of porous rocks", *International Journal of Rock Mechanics and Mining Sciences*, vol. 91, pp. 1-6, 2017.
- [28] J.A. Øverli, "A density-dependent failure criterion for concrete", *Construction and Building Materials*, vol. 124, pp. 566-574, 2016.
- [29] T. Kazerani, "Effect of micro mechanical parameters of micro structure on compressive and tensile failure process of rock", *International Journal of Rock Mechanics & Mining Sciences*, vol. 64, pp. 44-55, 2013.
- [30] X.Z. Li, Z.S. Shao, and L.F. Fan, "A micro-macro method for predicting the shear strength of brittle rock under compressive loading", *Journal Mechanics Research Communications*, vol.75, pp. 13-19, 2016.
- [31] H. Hofmann, T. Babadagli, J.S. Yoon, A. Zang, and G. Zimmermann, "A grain based modeling study of mineralogical factors affecting strength, elastic behavior and micro fracture development during compression tests in granites", *Engineering Fracture Mechanics*, vol. 147, pp. 261-275, 2015.
- [32] S.-Q. Yang, "Experimental study on deformation, peak strength and crack damage behavior of hollow sandstone under conventional triaxial compression", *Engineering Geology*, vol. 213, pp. 11-24, 2016.
- [33] A. Bubeck, R. Walker, D. Healy, M. Dobbs, and D. Holwell, "Pore geometry as a control on rock strength", *Earth and Planetary Science Letters*, vol. 457, pp. 38-48, 2017.
- [34] H. Li, and L.N.Y. Wong, "Influence of flaw inclination angle and loading condition on crack initiation and propagation", *International Journal of Solids and Structures*, vol. 49, pp. 2482-2499, 2012.
- [35] J. Jin, P. Cao, Y. Chen, C. Pu, D. Maod, and X. Fan, "Influence of single flaw on the failure process and energy mechanics of rock-like material", *Computers and Geotechnics*, vol. 86, pp. 150-162, 2017.
- [36] Y. Gui, Z. Zhao, C. Zhang, and S. Ma, "Numerical investigation of the opening effect on the mechanical behaviours in rocks under uniaxial loading using hybrid continuum-discrete element method", *Computers and Geotechnics*, vol. 90, pp. 55-72, 2017.
- [37] A. Fahimifar, "Deformational characteristics of rocks containing a single discontinuity", *International Journal of Engineering Transaction B: Applications*, vol. 15 (3), pp. 241-248, 2002.
- [38] H. Javdanian, "The effect of geopolymerization on the unconfined compressive strength of stabilized fine-grained soils", *International Journal of Engineering Transactions B: Applications*, vol. 30(11), pp. 1673-1680, 2017.
- [39] M. Shariati, N.H.R. Sulong, A. Shariati, and A.B.H. Kueh, "Comparative performance of channel and angle shear connectors in high strength concrete composites: an experimental study", *Construction and Building Materials*, vol. 120, pp. 382-392, 2016.
- [40] M.J. Ikari, A.R. Niemeijer, and C. Marone, "Experimental investigation of incipient shear failure in foliated rock", *Journal of Structural Geology*, vol. 77, pp. 82-91, 2015.
- [41] H. Xie, J. Pei, J. Zuo, and R. Zhang, "Investigation of mechanical properties of fractured marbles by uniaxial compression tests", *Journal of Rock Mechanics and Geotechnical Engineering*, vol. 3(4), pp. 302-313, 2011.
- [42] E. Hoek, C. Carranza-Torres, and B. Corkum, "Hoek-Brown failure criterion – 2002 edition" in *Proc. NARMS-TAC Conference*, Toronto, 2002.