

- [10] N. Syarif, I. A. Tribidasari, and W. Widayanti, "Binder-less activated carbon electrode from gelam wood for use in supercapacitors," *J Electrochem Sci Eng*, vol. 3, no. 2, pp. 37–45, 2014.
- [11] T. Kim *et al.*, "Applications of Voltammetry in Lithium Ion Battery Research," *J. Electrochem. Sci. Technol.*, vol. 11, no. 1, pp. 14–25, Feb. 2020, doi: 10.33961/jecst.2019.00619.
- [12] S. B. Aziz, T. J. Woo, M. F. Z. Kadir, and H. M. Ahmed, "A conceptual review on polymer electrolytes and ion transport models," *J. Sci. Adv. Mater. Devices*, vol. 3, no. 1, pp. 1–17, Mar. 2018, doi: 10.1016/j.jsamd.2018.01.002.
- [13] S. Farahani, "Battery Life Analysis," in *ZigBee Wireless Networks and Transceivers*, Elsevier, 2008, pp. 207–224.
- [14] A. Tomaszewska *et al.*, "Lithium-ion battery fast charging: A review," *eTransportation*, vol. 1, p. 100011, Aug. 2019, doi: 10.1016/j.etrans.2019.100011.
- [15] B. S. Vishnugopi, A. Verma, and P. P. Mukherjee, "Fast Charging of Lithium-ion Batteries via Electrode Engineering," *J. Electrochem. Soc.*, vol. 167, no. 9, p. 090508, Mar. 2020, doi: 10.1149/1945-7111/ab7fb9.
- [16] N. Elgrishi, K. J. Rountree, B. D. McCarthy, E. S. Rountree, T. T. Eisenhart, and J. L. Dempsey, "A Practical Beginner's Guide to Cyclic Voltammetry," *J. Chem. Educ.*, vol. 95, no. 2, pp. 197–206, Feb. 2018, doi: 10.1021/acs.jchemed.7b00361.
- [17] A. Ray, A. Roy, S. Saha, and S. Das, "Transition Metal Oxide-Based Nano-materials for Energy Storage Application," in *Science, Technology and Advanced Application of Supercapacitors*, T. Sato, Ed. IntechOpen, 2019.
- [18] T. Dobbelaere, P. M. Vereecken, and C. Detavernier, "A USB-controlled potentiostat/galvanostat for thin-film battery characterization," *HardwareX*, vol. 2, pp. 34–49, Oct. 2017, doi: 10.1016/j.ohx.2017.08.001.
- [19] C. Liu, Z. G. Neale, and G. Cao, "Understanding electrochemical potentials of cathode materials in rechargeable batteries," *Mater. Today*, vol. 19, no. 2, pp. 109–123, Mar. 2016, doi: 10.1016/j.mattod.2015.10.009.
- [20] T.-S. Chen, S.-L. Huang, M.-L. Chen, T.-J. Tsai, and Y.-S. Lin, "Improving Electrochemical Activity in a Semi-V-I Redox Flow Battery by Using a C–TiO₂–Pd Composite Electrode," *J. Nanomater.*, vol. 2019, pp. 1–11, Jan. 2019, doi: 10.1155/2019/7460856.
- [21] R. Subramani, Y.-H. Tseng, Y.-L. Lee, C.-C. Chiu, S.-S. Hou, and H. Teng, "High Li⁺ transference gel interface between solid-oxide electrolyte and cathode for quasi-solid lithium-ion batteries," *J. Mater. Chem. A*, vol. 7, no. 19, pp. 12244–12252, 2019, doi: 10.1039/C9TA02515D.
- [22] J. Menzel, E. Frąckowiak, and K. Fic, "Agar-based aqueous electrolytes for electrochemical capacitors with reduced self-discharge," *Electrochimica Acta*, vol. 332, p. 135435, Feb. 2020, doi: 10.1016/j.electacta.2019.135435.
- [23] L. S. Roselin *et al.*, "Recent Advances and Perspectives of Carbon-Based Nanostructures as Anode Materials for Li-ion Batteries," *Materials*, vol. 12, no. 8, p. 1229, Apr. 2019, doi: 10.3390/ma12081229.
- [24] R. Suarez-Hernandez, G. Ramos-Sánchez, I. O. Santos-Mendoza, G. Guzmán-González, and I. González, "A Graphical Approach for Identifying the Limiting Processes in Lithium-Ion Battery Cathode Using Electrochemical Impedance Spectroscopy," *J. Electrochem. Soc.*, vol. 167, no. 10, p. 100529, Jun. 2020, doi: 10.1149/1945-7111/ab95c7.
- [25] H. Lv, X. Huang, and Y. Liu, "Analysis on pulse charging–discharging strategies for improving capacity retention rates of lithium-ion batteries," *Ionics*, vol. 26, no. 4, pp. 1749–1770, Apr. 2020, doi: 10.1007/s11581-019-03404-8.