

REFERENCES

- [1] M. Minhat, S.B. Mohamed, M.S. Kasim, M.A. Sulaiman and Z.I. Rizman, "Advanced manufacturing of an aircraft component (fish-head): a technology review on the fabrication," *Int. J. Adv. Sci. Eng. Info. Technol.*, vol. 6 no. 5, pp. 734 – 739, 2016.
- [2] A.S. Pouzada, "Hybrid moulds: a case integration of alternative materials and rapid prototype for tooling," *Vir..and Phys. Proto.*, vol. 4, no. 4, pp. 195 – 202, 2009.
- [3] P. Dunne, S.P. Soe, G. Byrne, A. Venus and A.R. Wheatley, "Some demands on rapid prototypes used as master patterns in rapid tooling for injection moulding," *J. Mater. Process. Technol.*, vol. 150, pp. 201 – 207, 2004.
- [4] J.I. Segal, and R.I. Campbell, "A review of research into the effects of rapid tooling on part properties," *Rapid Prototyping J.*, vol. 7, no. 2, pp. 90 – 98, 2001.
- [5] Khurram. A, Ahmad M.A.R, and Vijay. R.R, "Prototype production and experimental analysis for circular and profiled conformal cooling channels in aluminium filled epoxy injection mould tools," *Rapid Prototyping J.*, vol. 19, no. 4, pp. 220 – 229, 2013.
- [6] P.V. Vasconcelos, F.J. Lino, A. Magalhães, Baptisa and R.J.L. Neto, "Impact fracture study of epoxy-based composites with aluminium particles and milled fibres," *J. Mater. Process. Technol.*, vol. 170, pp. 277 – 283, 2005.
- [7] "RenCast CW47 datasheet 2007," Huntsman Adv. Materials GmbH, Switzerland.
- [8] M.T.M. Khushairi, S. Sharif, and J.S.M. Ani, "Parameter design of hardness for metal filled epoxy matrix," *Adv. Mat. Res.*, vol. 1125, pp. 152-156, 2015.
- [9] "Handling procedure mould production with MCP tooling resins - EP 310 (ver. 3)," MCP-HEK Tooling GmbH, Germany.
- [10] N.S. Gokhale, S.S. Deshpance and S.V. Bedekar, A.N. Thite, *Practical Finite Element Analysis – 1st Edition, Finite to Infinite*, Pune, India, 2008.
- [11] J.P Holman, *Heat Transfer*, New York: McGraw Hill, 2001
- [12] T.L. Richardson and E. Lokensgard, *Industrial Plastics, Theory and Applications*, New York: Delmar Publishers Inc., 1996.
- [13] A.R. Wolfe and M.Weiner, "Compression testing - comparison of various test methods," *Composites convention and trade show*, 2004, American Composites Manufacturers Assoc., Tampa, USA.
- [14] M.S. Bhagyashekar, K. Rao and M.V.G.K. Rao, "Studies on rheological and physical properties of metallic and non-metallic particulate filled epoxy composites," *J. Reinf. Plast. Compos.*, vol. 28, pp. 2869 – 2878, 2009.
- [15] S. Ma, I. Gibson, G. Balaji, and Q.J. Hu, "Development of epoxy matrix composites for rapid tooling applications," *J. of Mat. Proc. Tech*, vol. 192-193, pp. 75-82, 2007.
- [16] S. Suresh, M.A. Jamil, S. Sulaiman and M.R.M. Shokor, "Optimization of electrode material for EDM die-sinking of Titanium Alloy grade 5 - Ti6Al4V," *Int. J. Adv. Sci. Eng. Info. Technol.*, vol. 6 no. 4, pp. 534 – 539, 2016.
- [17] T. Tomori, S. Melkote and M. Konis, "Injection mould performance of machined ceramic filled epoxy tooling boards," *J. Mater. Process. Technol.*, vol. 145, pp. 126-133, 2004.
- [18] M.S. Bhagyashekar, and M.V.G.K. Rao, "Characterization of mechanical behaviour of metallic and non-metallic particulate filled epoxy matrix composites," *J. Reinf. Plast. Compos.*, vol. 29, pp. 30 – 42, 2010.
- [19] M.T.M. Khushairi, S. Sharif, and J.S.M. Ani, "Evaluation of mechanical properties of filled epoxy composite for improving mould performance – a review," *Adv. Mat. Res.*, vol. 735, pp. 13 – 18, 2015.